

**Gprinter®**

Quality is for possibility | Innovation is for growth

## 4" Label Printer - Direct Thermal Series

GP-1924D



## Product Features

- User-friendly control
- 5 inch/s high speed printing
- Support 2D barcode and black mark printing
- Support media width from 40mm to 120mm
- Automatic paper calibration
- Automatic temperature control for durable printing
- Modular designs will satisfy different



Windows 10



## Specifications

MODEL	GP-1924D	
PRINTING	Print Method	Direct Thermal
	Print Speed	2~5 inch/s (51-127mm/s)
	Interface	USB
	Print Resolution	203 dpi
	Dot Size	0.125x0.125mm (1mm=8dots)
	Print Width	Max. 104mm (4.09")
	Print Length	Max. 2286mm (90")
	Printer Dimensions	285*210*180mm (WxDxH)
PHYSICAL PROPERTIES	Printer Weight	Approx. 2.09KG
	Operation Condition	Temperature: 5~45°C(41~104°F), Humidity: 25~85%RH
	Storage Condition	Temperature: -10~50°C(-10~140°F), Humidity: 10%~90%RH
	Print Head	50KM
	Power supply	Input: AC 110V/240V Output: DC24V/2.5A, 60W
	Media Roll OD	130mm OD
	Media Type	Continuous, black mark, gap, punched hole, Fan fold label etc.
	Media Rolling Up Method	Printing side outward rolling
MEDIA	Media Width (+Linner)	Max.120mm (4.72") Min.20mm (0.78")
	Media Thickness (+Linner)	Max. 0.254mm (10mil) Min. 0.06mm (2.36mil)
	Media Roll Core Size	25.4mm~38mm (1"~1.5")
	Media Gap	Min. 2 mm (0.09")
	Label Length	10~2286mm (0.39"~90")